



## EC Declaration of Conformity

### **We, the undersigned,**

Manufacturer : Teconex n.v.  
 Adress, City : Rue de Magnée, 108 4610 Beyne-Heusay  
 Country : Belgium  
 Telephone : 04 358 85 75  
 Mail : info@teconex.be



### **Certify and declare under our sole responsibility that the following apparatus:**

Description : residual current operated circuit-breakers type B  
 Manufacturer : Teconex  
 Brand : Teco  
 Identification : F9...GB/F9...SB (list of references : see appendix)

### **Conforms with the essential requirements of the Low Voltage Directive 2014/35/EC based on the following European Standards:**

**NBN EN 61008-1 based on 61008-1:2012**  
**NBN EN 61008-2-1 based on 61008-2-1:1994 + A11:1998**  
**NBN EN 62423:2013**  
**Belgian requirement: 22.5 kA<sup>2</sup>s / 3000A**

Year of CE-marking: 2017

Name and position of person binding the manufacturer or his authorized representative	March 19, 2017
 Mr. Axel Bervoets Product & Marketing Director Teconex s.a.	 Rue de Magnée, 108 4610 BEYNE-HEUSAY Belgium Tel: +32(0)4 358 85 75 N° entreprise BE0429 524 116 E-mail: info@teconex.be web: www.teconex.eu

Siège social/Maatschappelijke zetel  
**Teconex S.A./N.V.**  
 Rue de Magnée, 108 - 4610 Beyne-Heusay - Belgium  
 Tél.: +32 (0)4 358 85 75 - Fax: +32 (0)4 358 23 73  
 www.teconex.be

**Vlaanderen**  
 Spinnerslaan, 10 - 9160 Lokeren - Belgium  
 Tel.: +32 (0)9 245 09 56 - Fax: +32 (0)9 221 09 62  
 www.teconex.be

N° entreprise: BE0429524116 - RPM LIEGE - BNP PARISBAS FORTIS: BE86 2400 2371 1450 - BIC: GEBABEBB  
 ING: BE69 3400 1106 2078 - BIC: BBRUBEBB - KBC: BE73 4410 6243 0160 - BIC: KREDBEBB  
 CBC: BE75 1960 2966 2251 - BIC: CREGBEBB - CCP: BE79 0001 4191 4333 - BIC: BPOTBEB1

## RCCB's series F9...B

Reference	Description
F9254003GB	4P 25A 30mA standard B type - frequency tolerance up to 2 kHz
F925403GB	4P 25A 300mA standard B type -frequency tolerance up to 2 kHz
F925403SB	4P 25A 300mA selective B type - frequency tolerance up to 2 kHz
F9254003GBFQ	4P 25A 30mA standard B type for special applications - high frequency (50 kHz)
F925403GBFQ	4P 25A 300mA standard B type for special applications - high frequency (50 kHz)
F925403SBFQ	4P 25A 300mA selective B type for special applications - high frequency (50 kHz)
F9404003GB	4P 40A 30mA standard B type - frequency tolerance up to 2 kHz
F940403GB	4P 40A 300mA standard B type - frequency tolerance up to 2 kHz
F940403SB	4P 40A 300mA selective B type - frequency tolerance up to 2 kHz
F9404003GBFQ	4P 40A 30mA standard B type for special applications - high frequency (50 kHz)
F940403GBFQ	4P 40A 300mA standard B type for special applications - high frequency (50 kHz)
F940403SBFQ	4P 40A 300mA selective B type for special applications - high frequency (50 kHz)
F9634003GB	4P 63A 30mA standard B type - frequency tolerance up to 2 kHz
F963403GB	4P 63A 300mA standard B type - frequency tolerance up to 2 kHz
F963403SB	4P 63A 300mA selective B type -frequency tolerance up to 2 kHz
F9634003GBFQ	4P 63A 30mA standard B type for special applications - high frequency (50 kHz) tolerance
F963403GBFQ	4P 63A 300mA standard B type for special applications - high frequency (50 kHz) tolerance
F963403SBFQ	4P 63A 300mA selective B type for special applications - high frequency (50 kHz) tolerance

Siège social/Maatschappelijke zetel  
**Teconex S.A./N.V.**  
 Rue de Magnée, 108 - 4610 Beyne-Heusay - Belgium  
 Tél.: +32 (0)4 358 85 75 - Fax: +32 (0)4 358 23 73  
[www.teconex.be](http://www.teconex.be)

**Vlaanderen**  
 Spinnerslaan, 10 - 9160 Lokeren - Belgium  
 Tel.: +32 (0)9 245 09 56 - Fax: +32 (0)9 221 09 62  
[www.teconex.be](http://www.teconex.be)

**N° entreprise:** BE0429524116 - **RPM LIEGE** - **BNP PARISBAS FORTIS:** BE86 2400 2371 1450 - **BIC:** GEBABEBB  
**ING:** BE69 3400 1106 2078 - **BIC:** BBRUBEBB - **KBC:** BE73 4410 6243 0160 - **BIC:** KREDBEBB  
**CBC:** BE75 1960 2966 2251 - **BIC:** CREGBEBB - **CCP:** BE79 0001 4191 4333 - **BIC:** BPOTBEB1

## Legend of commercial references

### F9-

25			Rated current: 25A
40			Rated current: 40A
63			Rated current: 63A
	4		Number of poles: 4
		003	Sensibility: 30mA
		03	Sensibility: 300mA
		<b>GB</b>	standard type B
		<b>SB</b>	selective + type B
		FQ	HF tolerance (50 kHz)