


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:35.000V I:1.4000A P:49.000W PF:1.0000 Freq:0Hz Lamp Flux:6148.7x1 lm		
NAME: LTY40X612CT19 1400mA_3000K	TYPE: YALA ONE	WEIGHT:
SPEC.:	DIM.: 600x1200x12	SERIAL No.:1
MFR.: TECONEX	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 125.48 lm/W			
MODEL	LTY40X612CT19	I _{max} (cd)	2674	S/MH(C0/180)	1.26
NOMINAL POWER(W)	54	LOR(%)	100.0	S/MH(C90/270)	1.35
RATED VOLTAGE(V)	35	TOTAL FLUX(lm)	6148.7	η UP,DN(C0-180)	0.0,50.0
NOMINAL FLUX(lm)	6148.7	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,50.0
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	35	η down(%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PLANAR ISOLUX DIAGRAM(UNIT:lx)



C Range: 0 - 90DEG
 C Interval: 5.0DEG
 Test Speed: MEDIUM
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2021-07-15

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
 Humidity:65.0%
 Test Distance:10.270m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	2593	2622	2638	2622	2593	2622	2638	2622	0- 10	249.4	249.4	4.06, 4.06
20	2499	2580	2674	2580	2499	2580	2674	2580	10- 20	740.1	989.4	16.1, 16.1
30	2241	2379	2608	2379	2241	2379	2608	2379	20- 30	1157	2146	34.9, 34.9
40	1707	1809	2122	1809	1707	1809	2122	1809	30- 40	1365	3511	57.1, 57.1
50	1090	1078	1168	1078	1090	1078	1168	1078	40- 50	1117	4628	75.3, 75.3
60	559.3	584.8	519.7	584.8	559.3	584.8	519.7	584.8	50- 60	710.5	5338	86.8, 86.8
70	352.5	322.0	368.5	322.0	352.5	322.0	368.5	322.0	60- 70	442.6	5781	94, 94
80	198.8	176.0	179.0	176.0	198.8	176.0	179.0	176.0	70- 80	274.3	6055	98.5, 98.5
90	0	0	0	0	0	0	0	0	80- 90	93.43	6149	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 4228 lm

%lum = 68.8%

%lamp = 68.8%

Conical surface Flux(120deg): 5338.4 lm

%lum = 86.8%


%lamp = 86.8%

C Range: 0 - 90DEG
 C Interval: 5.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2021-07-15

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.295
 Humidity: 65.0%
 Test Distance: 10.270m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:35.000V I:1.4000A P:49.000W PF:1.0000 Freq:0Hz Lamp Flux:6148.7x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:




C Range: 0 - 90DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:DAMIN
Test Date:2021-07-15

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:35.000V I:1.4000A P:49.000W PF:1.0000 Freq:0Hz Lamp Flux:6148.7x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.06	1.02	.99	1.04	1.00	.97	.99	.97	.94	.96	.93	.91	.92	.90	.88	.86
2.0	.94	.88	.83	.92	.87	.82	.89	.84	.80	.86	.82	.78	.83	.79	.76	.74
3.0	.84	.77	.71	.82	.76	.70	.80	.74	.69	.77	.72	.68	.74	.70	.67	.65
4.0	.75	.67	.61	.74	.67	.61	.72	.65	.60	.69	.64	.59	.67	.63	.59	.57
5.0	.68	.60	.54	.67	.59	.54	.65	.58	.53	.63	.57	.52	.61	.56	.52	.50
6.0	.62	.54	.48	.61	.53	.48	.59	.52	.47	.58	.51	.47	.56	.51	.46	.44
7.0	.57	.48	.43	.56	.48	.43	.54	.47	.42	.53	.47	.42	.52	.46	.42	.40
8.0	.52	.44	.38	.51	.44	.38	.50	.43	.38	.49	.42	.38	.48	.42	.38	.36
9.0	.48	.40	.35	.47	.40	.35	.46	.39	.35	.45	.39	.34	.44	.38	.34	.33
10.0	.44	.37	.32	.44	.37	.32	.43	.36	.32	.42	.36	.31	.41	.35	.31	.30



C Range: 0 - 90DEG
 C Interval: 5.0DEG
 Test Speed: MEDIUM
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2021-07-15

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
 Humidity:65.0%
 Test Distance:10.270m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:35.000V I:1.4000A P:49.000W PF:1.0000 Freq:0Hz Lamp Flux:6148.7x1 lm					
NAME:		TYPE:		WEIGHT:	
SPEC.:		DIM.:		SERIAL No.:1	
MFR.: EVERFINE		SUR.:		Shielding Angle:	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.272	.155	.049	.265	.151	.048	.252	.145	.046	.240	.138	.044	.229	.133	.043		
2.0	.257	.141	.043	.251	.138	.043	.240	.133	.041	.229	.129	.040	.220	.124	.039		
3.0	.241	.128	.038	.235	.126	.038	.225	.122	.037	.216	.118	.036	.207	.115	.036		
4.0	.224	.117	.034	.220	.115	.034	.211	.112	.033	.203	.109	.033	.195	.106	.032		
5.0	.210	.107	.031	.205	.105	.031	.198	.103	.030	.190	.100	.030	.183	.098	.029		
6.0	.196	.098	.028	.192	.097	.028	.185	.095	.028	.179	.093	.027	.173	.091	.027		
7.0	.184	.091	.026	.181	.090	.026	.175	.088	.025	.169	.086	.025	.163	.085	.025		
8.0	.173	.085	.024	.170	.084	.024	.165	.082	.023	.159	.081	.023	.154	.079	.023		
9.0	.163	.079	.022	.161	.078	.022	.156	.077	.022	.151	.076	.022	.146	.074	.022		
10.0	.154	.074	.021	.152	.073	.020	.148	.072	.020	.143	.071	.020	.139	.070	.020		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.178	.156	.137	.152	.134	.118	.104	.092	.082	.060	.053	.048	.019	.017	.015	
2.0	.168	.132	.102	.144	.114	.088	.098	.079	.062	.057	.046	.036	.018	.015	.012	
3.0	.159	.114	.078	.136	.098	.068	.093	.068	.048	.054	.040	.028	.017	.013	.009	
4.0	.151	.100	.062	.129	.087	.054	.089	.060	.038	.051	.035	.022	.017	.012	.007	
5.0	.143	.090	.050	.123	.078	.044	.085	.054	.031	.049	.032	.018	.016	.010	.006	
6.0	.136	.081	.042	.117	.070	.036	.081	.049	.026	.047	.029	.015	.015	.009	.005	
7.0	.130	.074	.035	.112	.064	.031	.077	.045	.022	.045	.027	.013	.014	.009	.004	
8.0	.124	.068	.030	.107	.059	.026	.074	.042	.019	.043	.025	.011	.014	.008	.004	
9.0	.118	.063	.026	.102	.055	.023	.071	.039	.016	.041	.023	.010	.013	.007	.003	
10.0	.113	.059	.023	.097	.051	.020	.067	.036	.015	.039	.021	.009	.013	.007	.003	

C Range: 0 - 90DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:DAMIN
Test Date:2021-07-15

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:35.000V I:1.4000A P:49.000W PF:1.0000 Freq:0Hz Lamp Flux:6148.7x1 lm										
NAME:					TYPE:			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:1		
MFR.: EVERFINE					SUR.:			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	14.2	15.6	14.5	15.8	16.0	14.6	16.0	14.9	16.2	16.4
3H	15.2	16.5	15.5	16.7	16.9	15.5	16.7	15.7	16.9	17.2
4H	15.7	16.9	16.0	17.1	17.4	15.9	17.1	16.2	17.3	17.5
6H	16.2	17.3	16.5	17.6	17.9	16.3	17.4	16.6	17.7	18.0
8H	16.4	17.5	16.8	17.8	18.1	16.4	17.5	16.8	17.8	18.1
12H	16.6	17.7	17.0	18.0	18.3	16.5	17.6	16.9	17.8	18.1
4H 2H	14.6	15.8	14.9	16.0	16.3	14.9	16.1	15.2	16.3	16.6
3H	15.8	16.8	16.1	17.1	17.4	16.0	17.0	16.3	17.3	17.6
4H	16.5	17.4	16.8	17.7	18.1	16.5	17.5	16.9	17.8	18.1
6H	17.2	18.0	17.6	18.4	18.7	17.1	17.9	17.5	18.3	18.7
8H	17.5	18.3	17.9	18.7	19.0	17.3	18.1	17.7	18.5	18.8
12H	17.8	18.5	18.2	18.9	19.3	17.5	18.2	17.9	18.6	19.0
8H 4H	16.7	17.5	17.1	17.9	18.3	16.8	17.6	17.2	17.9	18.3
6H	17.7	18.3	18.1	18.7	19.2	17.5	18.2	18.0	18.6	19.0
8H	18.1	18.7	18.6	19.1	19.6	17.8	18.4	18.3	18.8	19.3
12H	18.5	19.0	19.0	19.4	19.9	18.1	18.6	18.5	19.0	19.5
12H 4H	16.8	17.5	17.2	17.9	18.3	16.8	17.5	17.2	17.9	18.3
6H	17.8	18.3	18.2	18.8	19.2	17.6	18.2	18.1	18.6	19.1
8H	18.3	18.7	18.7	19.2	19.7	18.0	18.5	18.4	18.9	19.4
Variations with the observer position at spacings:										
S = 1.0H	+ 0.4 / - 0.4					+ 0.4 / - 0.6				
1.5H	+ 0.2 / - 0.4					+ 0.4 / - 0.3				
2.0H	+ 0.7 / - 0.6					+ 1.1 / - 0.8				

CIE Pub.117, 6149 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 6.3$)

C Range: 0 - 90DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:DAMIN
Test Date:2021-07-15

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:35.000V I:1.4000A P:49.000W PF:1.0000 Freq:0Hz Lamp Flux:6148.7x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	65	55	48	64	54	48	63	54	48	42
0.80	75	65	58	74	64	58	72	63	58	51
1.00	82	73	67	81	72	66	79	73	66	60
1.25	89	80	74	88	79	73	85	78	73	66
1.50	93	85	79	92	84	79	89	82	77	71
2.00	99	92	86	97	91	86	94	89	84	77
2.50	102	96	90	100	94	90	97	92	88	80
3.00	105	99	94	103	98	93	99	95	91	83
4.00	108	103	99	106	102	98	102	98	95	87
5.00	110	106	103	108	104	101	104	101	98	89
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 90DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:DAMIN
Test Date:2021-07-15

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:35.000V I:1.4000A P:49.000W PF:1.0000 Freq:0Hz Lamp Flux:6148.7x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:




C Range: 0 - 90DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2021-07-15

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity: 65.0%
Test Distance: 10.270m [K=1.0000]
Remarks:

AAI Figure

Test:U:35.000V I:1.4000A P:49.000W PF:1.0000 Freq:0Hz Lamp Flux:6148.7x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 90DEG
 C Interval: 5.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2021-07-15

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.295
 Humidity: 65.0%
 Test Distance: 10.270m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:35.000V I:1.4000A P:49.000W PF:1.0000 Freq:0Hz Lamp Flux:6148.7x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



C Range: 0 - 90DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:DAMIN
Test Date:2021-07-15

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:35.000V I:1.4000A P:49.000W PF:1.0000 Freq:0Hz Lamp Flux:6148.7x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	1347
L_0~180 (75) av	1452
L_0~180 (85) av	1722
L_90~270 (65) av	1479
L_90~270 (75) av	1419
L_90~270 (85) av	1262
L_45 (65) av	1476
L_45 (75) av	1339
L_45 (85) av	1214

Standard: GB/T 29293-2012

C Range: 0 - 90DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:DAMIN
Test Date:2021-07-15

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 90DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2021-07-15

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity: 65.0%
Test Distance: 10.270m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

```

```

Range: 0 - 90DEG
Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

```